

REVERSE OSMOSIS

BEVERAGE INDUSTRY

STANDARD FEATURES

- Pretreatment and Polishing processes integrated into one system
- Vertical multistage pumps are longer-lasting and provide a higher level of reliability
- Convenient sample ports on each housing for easy quality monitoring
- Comprehensive Factory Acceptance Testing (FAT) performed in our ISO9001 certified facility
- Fully programmable alarm conditions customized to your system requirements
- Hot water sanitizable units are available
- Allen Bradley PLC and Touchscreen HMI for easy monitoring and seamless integration with existing equipment
- Aqua-Chem's field service team supports you during and after commissioning.
- Clean in Place- Full machine or bank-by-bank capability



Aqua-Chem's range of Reverse Osmosis (RO) Systems are the result of decades of experience engineering complete water rooms to create the most efficient and sustainable systems to produce purified ingredient water for the beverage industry. Aqua-Chem Reverse Osmosis Systems are highly customizable utilizing a wide range of membranes from a variety of suppliers.

This flexibility means that Aqua-Chem can balance all aspects of the purification process at your facility; feed water conditions, permeate quality requirements, energy consumption, and recovery goals to create the most efficient and sustainable system for your facility.

CONTACT US:

(800) 964-7035

sales@aquachem.com

www.aquachem.com

3001 E. Governor John Sevier Hwy
Knoxville, TN 37914



REVERSE OSMOSIS

MODEL	Beverage RO-100	Beverage RO-200	Beverage RO-300	Beverage RO-400	Beverage RO-75	Beverage RO-150	Beverage RO-250	Beverage RO-350
Design Capacity	Single Pass	Single Pass	Single Pass	Single Pass	Double Pass	Double Pass	Double Pass	Double Pass
Nominal Product Flow Range (gpm)	60-110	150-205	220-315	315-415	75-100	150-185	220-285	315-375
RO Design Recovery (%)	80	80	80	80	80	80	80	80
w/Conc. Recovery Option (%)	up to 90	up to 90	up to 90	up to 90	up to 90	up to 90	up to 90	up to 90
Nominal Salt Rejection (%)	up to 99	up to 99	up to 99	up to 99	up to 99	up to 99	up to 99	up to 99
Feed Water Temperature (*F)	77	77	77	77	77	77	77	77
Operating Parameters * *								
Operating Temperature (*F)	50 to 77	50 to 77	50 to 77	50 to 77	50 to 77	50 to 77	50 to 77	50 to 77
Max. Operating Pressure (psi)	300	300	300	300	300	300	300	300
Operating pH Range (pH units)	5-7	5-7	5-7	5-7	5-7	5-7	5-7	5-7
Nominal Feed Water Flow (gpm)	125	250	375	500	113	167	375	500
Membrane Elements Energy Savings								
Membrane Surface Area (ft2)	400	400	400	400	400	400	400	400
Vessel Length (membrane/vessel)	6	6	6	6	6	6	6	6
Vessel Array (Pass 1)	2:1:1	4:2:1	6:3:2	8:4:2	2:1:1	4:2:1	6:3:2	8:4:2
Membrane Quantity (Pass 1)	24	42	66	84	24	42	66	84
Vessel Array (Pass 2)	N/A	N/A	N/A	N/A	2:1	3:1	5:2	6:3
Membrane Quantity (Pass 2)	N/A	N/A	N/A	N/A	18	24	42	54
Pumps Vertical Multistage Centrifugal Pumps								
Motor (HP) (Pass 1)	25 HP	50 HP	75 HP	100 HP	25 HP	50 HP	75 HP	100 HP
Motor (HP) (Pass 2)	N/A	N/A	N/A	N/A	25 HP	50 HP	75 HP	100 HP
Terminal Point Connections								
Feed	3" Tri-Clamp	4" Tri-Clamp	6" Tri-Clamp	6" Tri-Clamp	3" Tri-Clamp	3" Tri-Clamp	6" Tri-Clamp	6" Tri-Clamp
Concentrate	1.5" Tri-Clamp	2" Tri-Clamp	2" Tri-Clamp	3" Tri-Clamp	1.5" Tri-Clamp	2" Tri-Clamp	2" Tri-Clamp	3" Tri-Clamp
Permeate	3" Tri-Clamp	3" Tri-Clamp	4" Tri-Clamp	6" Tri-Clamp	2" Tri-Clamp	3" Tri-Clamp	4" Tri-Clamp	6" Tri-Clamp
Electrical								
High Voltage (Pumps and Motors) ***	480V, 60Hz, 3Ph							
Low Voltage (Control Panel) ***	120V, 60Hz, 1Ph							
System Dimensions								
L x W x H (in)	268 x 53 x 72	268 x 53 x 74	268 x 84 x 72	268 x 90 x 87	288 x 75 x 72	268 x 80 x 74	288 x 96 x 74	288 x 108 x 87
Est. Dry Shipping Weight (lb)	3,860	5,000	7,900	8,350	4,350	5,120	9,000	9,815
Est. Wet Op. Weight (lb)	6,800	12,400	15,000	18,000	9,200	12,400	21,000	25,000

Additional Flow Rates and Customizations are Available.

*Treatment ability of the RO system is dependent on feed water quality.

***Consult Aqua-Chem Inc. for other voltage options.

****Feed Water Source Requirements:**

- System is based on municipal feed water
- Temperature: 50 to 77°F
- Pressure: 30 to 80 psig
- NTU <1
- SDI <3
- TOC <3 ppm
- Free Chlorine <0.1 ppm
- Iron/ Manganese <0.1 ppm
- TDS <500 ppm
- Oil & Grease <0.1 ppm
- Silica <10 ppm
- Aluminum <0.5 ppm
- CO2 <12 PPM

Higher TDS and/or lower temperatures will reduce product flow. An Aqua-Chem Applications Engineer can rate the units for other feed water conditions.